



KPOS Scout

Pistol Conversion Kit for Glock 17/19

Retail/Bulk:

- BULK
- Retail

Color:

- Black
- Flat Dark Earth
- Olive Drab Green
- Grey

LOCATE DISTRIBUTOR

Product Description

- The KPOS Scout incorporates a hybrid construction, combining a rigid aluminum upper with a lightweight polymer lower, for a compact yet extremely durable and accurate handgun conversion kit. The KPOS Scout upper is machined from 6061 T6 aluminum, with a full length, integrated 1913 MIL-STD Picatinny rail, for ultimate stability with any mounted optics and sights. The

aluminum upper also allows the Scout to be safely used with ported Glock models (G17C, G19C) The KPOS Scout lower is made of reinforced polymer composite for improved versatility and weight reduction and incorporates a new "one button" assembly design. Available in two configurations, KPOS Scout and KPOS Scout Advanced. KPOS Scout: FGG-KPOS Folding foregrip & trigger cover SLS QD sling swivel Bungee, one point tactical sling KPOS Scout Advanced: FGG-KPOS Folding foregrip & trigger cover SLS QD sling swivel Bungee, one point tactical sling Set of polymer backup sights FBS & RBS KPOS carry bag

Product Advantages

- New hybrid design, aluminum & polymer Extremely light weight, easily concealable and compact Quick and easy installation requires no tools or handgun modification Can be used with Glock 17 or 19 with no modifications to the handgun or to the KPOS Scout Snap locking mechanism- single button for quick, easy and secure assembly Ambidextrous M4 style charging handle Full length 1913 MIL-STD Picatinny rail upper, short polymer lower rail and two removable side rails with integrated thumb rests Vertical foregrip folds to horizontal position and incorporates an extendable trigger guard Folding buttstock with high traction rubber butt-pad Hard anodized solid 6061 T6 Aluminum upper Reinforced polymer lower and buttstock / brace Competitive pricing available in two versions, KPOS Scout and KPOS Scout Advanced Limited Lifetime warranty

Compatibility

- Glock models 17, 19, 19X, 22, 23, 25, 31, 32, 45 / Gen 3 - 5 including 'C' Models, without a backstrap grip add-on.

Specifications

Length	326 mm
Width	73 mm
Height	170 mm
Length deployed	542 mm
Width deployed	60 mm
Weight	720 gr