



SPIKE

Precision Bipod

[LOCATE DISTRIBUTOR](#)

Product Description

The SPIKE was designed to deliver the best experience and comfort to any mission via its versatility and smart hybrid construction

Product Advantages

- Smart hybrid construction, hardened steel, 6061 T-6 aluminum & high-performance polymer composites
- 4 locking leg positions: 0, 45, 90 & 135 degrees
- Adjustable rotating head with tilt and pan adjustments that can be locked down or released for quick target tracking
- 60 degrees pan movement with a spring-loaded mechanism
- 20 degrees tilt movement
- Leg height range of 180 mm to 251 mm (height measured at the 90° leg position)
- Quick leg height increase with a simple pull down of the leg extension
- Quick leg height decrease with a push of a button
- Rectangular shaped inner legs for enhanced stability & rigidity
- Rubberized feet for secure surface grip
- Quick & tool-less replacement of feet
- Foot print of 245 to 300 mm
- Additional leg height extension included

Compatibility

- 1913 Picatinny Rail compatible

Specifications

Length	206 mm
Width	96 mm
Height	50 mm
Length deployed	51 mm
Width deployed	242 mm
Height deployed	188 mm
Max height deployed	255 mm
Max width deployed	308 mm

Weight

405 gr

